

# XRF-R.2

Part No. 407692

DATASHEET

Receiver to wireless transmission system of ExpertSystem

## Receiver with two safety outputs

### Mechanical data

Dimensions	121 x 75 x 24 mm
Material (housing)	ASA light grey
Terminals	12, push-in spring connection conductor cross section 0.25 – 0.75 mm <sup>2</sup>
Cable strain relief	Built in (for cable-Ø 3.1 to 5.2 mm)
Weight in gr	200

### Electrical data

Supply voltage	12-36 V ACDC, 48-62 Hz
Power consumption	0.7 W at 12 V, 1.0 W at 36 V
Test input (for Cat. 2 applications)	12-36 V ACDC, 5.5 mA at 24 V
Sensor memory	2 x 7 sensor elements
Outputs	2 x 2 relays 36 V ACDC, 1 A
Options	NO with parallel resistor 8,2 kOhm NC
Displays	2 LEDs bicoloured (status output, programming)
Joystick (for pairing)	5 positions
Dip-switch (test input)	factory setting: OFF (= high active)

### In combination with XRF transmitters

Range in m	100 at optimum conditions
Reaction time	Typ. 15 ms
Communication	Bidirectional
Operating frequency	868.3 MHz
Radiated power	< 10 dbm / 10 mW
Low battery indication	Acoustic and optical (on the receiver)

### Approvals

EN 300 220, EN 301 489	
EN ISO 13849-1 (PLd, Cat.3, MTTFd 153)	Add. Test input for Cat. 2 applications

### Ambient conditions

Protection category	IP65
Operating temperature	-20°C to +60°C
Storage temperature	-40°C to +80°C
Rel. air humidity	< 95%, non-condensing



### Box contents

Receiver, 6 instruction manuals (DE, EN, FR, IT, NL, SV), mounting material

### Dimensions

