




B101 BIRDGUARD

Addon camera for DoorBird IP Video Door Station









Open API

Local interface for the integration with third-party systems and SIP



WiFi enabled

Works within a WiFi network, no LAN cable needed



Smart Transmission Mode (STM)

Real-time audio / video communication, optimized for mobile devices via WiFi, 3G, 4G, 5G



Burglary prevention

Prevents more break-ins than an alarm system



Easy self-installQuick installation via
QR code scan

TECHNICAL SPECIFICATIONS



GENERAL

Material Polycarbonat

15 V DC (power supply 110 - 240 V AC)

Power supply or Power over

Ethernet (PoE 802.3af Mode-A)

Weight 290 g

· RJ45, for LAN/PoE

15 V DC input (+, -), max. 15 W

· External input,

Connectors e.g. motion sensor, external

speaker

· Switching relay (potential-free), e.g. for garage door, sirens/alarm

Weather-proof Yes, IP65

Approvals CE, IC, FCC, RoHS, IP65

125 x 75 x 35 mm (H x W x D) **Dimensions**

4,92 x 2,95 x 1,38 in (H x W x D)

-20 to +40°C / -4 to 104°F

Operating conditions Humidity 10 to 85 % RH

(non condensing)

1x Main Electrical Unit

2x Antenna

1x Mounting stand

1x Power supply unit (mains adaptor) with four country-specific outlet adaptors

Scope of delivery (110 - 240 V AC to 15 V DC)

1x Screwdriver

1x Quickstart guide with

Digital Passport 1x Installation manual 1x Small parts

4260423860025 EAN

see www.doorbird.com/warranty Warranty

CURRENT SYSTEM REQUIREMENTS

Mobile device: Newest iOS on iPhone/iPad, newest Android on

Smartphone/Tablet

System requirements Internet: High-Speed Landline Broadband

Internet connection, DSL, cable or fiber

optic, no socks or proxy server

Network: Ethernet Network, with DHCP

VIDEO

HDTV 720p, dynamic (VGA - HDTV) Camera

High-end ultra wide-angle hemispheric Lens

lens 180° horizontal, 90° vertical, straightened, IR-capable

Yes, light sensor, automatic IR-cut filter, Night-vision

12 IR-LEDs (850 nm)

AUDIO

Speaker and microphone, echo and

noise cancellation (AEC, ANR),

integrated amplifier for connecting **Audio components** an external high-performance passive

speaker

Two-way, full duplex **Audio streaming**

NETWORK

802.11 b/g/n 2.4 GHz WiFi Ethernet Connector, PoE

MOTION SENSOR

Type Passiv infrared sensor (PIR)

Detection angle 180°

2 - 8 m (79 - 315 in) Range

depends on environment

INTEGRATED WIRELESS MODULES

WiFi 2,4 GHz, internal antenna

OPTIONAL ACCESSORIES

Sold separately see www.doorbird.com/buy